

PRODUCT CODE: NSM-7300 BARCODE: 9332820002966

PRODUCT DESCRIPTION

Heavy Duty 7" Colour TFT LCD Monitor with 3 camera inputs

NARRATIVE

When a solid robust widescreen is required, look no further. The NSM-7300 has proven itself in the harshest conditions over a prolonged period of time & is our 1st recommendation for extreme conditions such as mining. With double mount gimble nuts on each side & a rubberised finish, this screen is built to last.

The NSM-7300 will accept 12v or 24v inputs & then feeds 12v out to each camera, eliminating the need to add voltage reducers to the system.

Each input has a separate trigger wire which allows for just about any application (reverse/left/right indicator

For flush mount applications a mounting kit is supplied as standard.

SPECIFICATIONS

Screen: 7" LCD monitor with digital panel	Video Swiching: 3 x triggers
Internal Speaker: Yes	Voltage: 12/24v DC
Video Inputs: 3 x AV RCA + 1 front 3.5mm	Power consumption: Approx 6W
Brightness: 400cd/m2	Dimension (mm): 182 x 122 x 26
Dot Pitch: 0.192 (H) x 0.1805 (V)	Operating temperature: -20° - +70°
Resolution: 800 x 3 (RGB) x 480	Contrast: 500:1
Viewing Angle: U-50°, D-60°, R/L- 70°/70°	Video Formats: PAL/NTSC Auto
Button Backlighting: Yes	Mount Options: U Bracket & Flush Mount Shroud
Also Available:	

NSM-7400Q Quad Monitor (up to 4 images on screen at once)

NSM-7450DVR Quad Monitor with SD Recording (up to 4 images on screen at once)

DATE OF PRODUCT RELEASE: 2009